



# Floor standing unit

FVXS-F



Online controller  
via app



VRV for residential  
application

## Floor standing unit for optimal heating comfort thanks to dual airflow

- › Can be installed against a wall or recessed
- › Its low height enables the unit to fit perfectly beneath a window
- › Online controller (optional): control your indoor from any location with an app, via your

- local network or internet and keep an overview on your energy consumption
- › Whisper quiet in operation down to 23 dBA
- › Seasonal efficiency values up to A+ in cooling and heating

# FVXS-F + RXL-M3



Indoor unit		FVXS	25F	35F
Casing	Colour		White	
Dimensions	Unit	HeightxWidthxDepth	mm	
			600x700x210	
Sound power level	Cooling		52	
	Heating		52	
Sound pressure level	Cooling	High/Low/Silent operation	38/26/23	
	Heating	High/Low/Silent operation	38/26/23	
Control systems	Infrared remote control		ARC452A1	


Efficiency data		FVXS + RXL	25F + 25M3	35F + 35M3	
Cooling capacity	Nom.	kW	2.5	3.5	
Heating capacity	Nom.	kW	4.5	5.6	
Power input	Heating	Nom.	1.19	1.62	
Seasonal efficiency (according to EN14825)	Cooling	Energy efficiency class	A		
		Pdesign	2.50	3.50	
		SEER	5.10	5.21	
	Heating (Average climate)	Annual energy consumption	kWh	173	235
		Energy efficiency class		A+	A
		Pdesign	kW	2.90	3.20
Nominal efficiency	EER		3.38	3.27	
		COP	3.78	3.46	
	Annual energy consumption	kWh	370	535	
	Energy labeling	Cooling		A	
		Heating		A	B

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load | Maximum heating capacity at -15°C outdoor temperature

Outdoor unit		RXL	25M3	35M3
Dimensions	Unit	HeightxWidthxDepth	mm	
			550x858x330	
Sound power level	Cooling		61	
	Heating		61	
Sound pressure level	Cooling	High/Low	48/44	
	Heating	High/Low	49/45	
Operation range	Cooling	Ambient	Min.-Max.	°CDB
	Heating	Ambient	Min.-Max.	°CWB
			-10~-46	-25~-18
Refrigerant	Type/Charge/GWP		kg/TCO <sub>2</sub> eq	
			R-410A/1/2.1/2,087.5	
Power supply	Phase/Frequency/Voltage		Hz/V	
			1~/50/220-240	

Contains fluorinated greenhouse gases

**Daikin Europe N.V.** Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · [www.daikin.eu](http://www.daikin.eu) · BE 0412 120 336 · RPR Oostende (Responsible Editor)



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)

ECPEN16-033

01/17



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.